

DISPLAY FILMS
Magic® DMBF5UV *New Improved*
9 Mil Frontprint / Backlit Polyester Film

Making all Great Images Count



www.magicinkjet.com

MARKET APPLICATIONS

- High quality indoor and outdoor durable backlit signage
- Backlit / frontlit trade show displays & and retail displays
- Indoor and outdoor applications
- Durable reflective signage

PRODUCT DESCRIPTION

- 9 mil backlit film
- Light diffusion layer is the ink jet receiver layer
- Image is positive-reading on matte surface, with pigment or dye inks
- Gloss polyester on reverse side

GENERAL AVAILABILITY

<u>DMBF5UV</u>	<u>Part #</u>
36" x 10'	45939
36" x 100'	45857
42" x 100'	45941
50" x 100'	45943
60" x 100'	45946

FEATURES & BENEFITS

- Positive direct-print on matte surface for easy file mgmt
- High color gamut on viewing side
- Can be frontlit or backlit – your choice
- Aqueous pigment & dye ink compatibility
- Best with pigment inks
- Waterfast coating with pigment ink for durable signage
- Optimized opacity for maximum color without hot spots

MEDIA COMPATIBILITY

Designed to offer exceptional print performance on Hewlett-Packard DesignJet® series, Epson Stylus® Pro 7800, 9800 with K3 inks, and Canon iPF 8000 printers.

- * For complete Magic® product set, refer to Magic Printer Compatibility Chart under Technical Support on www.magicinkjet.com.
- * For additional product details – including printer settings and lamination guidelines – see Application Guide under Tech Support of www.magicinkjet.com
- * For ICC profile availability, see www.magicinkjet.com

Phone: 1-800-628-8604

Fax: 1-800-861-4128

Disclaimer: Information presented in this product sell sheet is intended to offer a useful reference in selecting media for your output. No media warranties are implied unless specifically mentioned. Printer and / or ink changes may affect results. The most current product information may be found at www.magicinkjet.com.

Date: April 2009

InteliCoat Technologies®

MAGIC® PRODUCT APPLICATIONS GUIDE

InteliCoat



Digital Imaging
Substrates

New Improved DMBF5UV

FRONTPRINT / BACKLIT POLYESTER FILM

MAGIC® New Improved DMBF5UV is a 9 mil bright white polyester film compatible with a wide variety of wide format ink jet printers and is designed for use with pigmented inks. Direct imaging on the front (matte) surface yields images with maximum ink density, vivid color and high image resolution for either reflective or backlit viewing in both indoor and outdoor applications. The combination of DMBF5UV's water-fastcoating and pigmented inks makes DMBF5UV ideal for outdoor signage.

PHYSICAL PROPERTIES

Caliper.....9.0 mil.....179 micron	Gloss of print side (60°)2.4
Opacity.....78%	Optimum Printing Environment.....70°F / 21°C (30-70% RH)
Whiteness(backing).....118	Protected Life Expectancy.....2 year indoor/1 year outdoor

PRINTING GUIDELINES

Printing: Print side is the matte side, and is wound to the outside of the roll. The print is front imaged and viewed from the image side.

Printer & Ink Compatibility: DMBF5UV is compatible with Hewlett-Packard DesignJet® series, Canon iPF series, and water-based piezo printers. Using pigment inks will yield outstanding print quality for use with either reflective or transmitted light.

Printer Settings: To optimize print quality, printers should be set for highest print quality. To reduce the effects of the star wheel marks and to minimize bleed, the recommended ink saturation level is 300% on the HP DesignJet series printers. The HP media setting is Backlit. Super and Bi-directional are the printer settings for the water-based piezo printers. Dry-time will vary depending on ink type and the ink saturation level used.

Water Resistance: DMBF5UV in conjunction with pigment inks has excellent water resistance. Lamination is not required but is recommended when an image will be exposed to repeated moisture or physical handling or when prolonged product life is needed. Dye based inks have a moderate level of water resistance. Condensation in a light box will not affect the image. DMBF5UV should be installed with the UV stable laminate side facing out.

Material Handling & Storage: Unused material should be stored in its original packaging, in the poly bag at 59-86°F / 15-30°C, and 30-70% RH.

FINISHING RECOMMENDATIONS

Image Protection: Due to the waterfast coating, lamination is not required, although overlaminates will protect the image from physical damage if the image is unprotected by glass. Cold pressure laminates should be used with DMBF5UV. A UV stable laminate is recommended.

Lighting: Viewing with reflective or transmitted light yields outstanding image contrast and color vibrancy.

RECYCLING AND DISPOSAL

 Disposal by recycling of ink jet media is the preferred method. Where recycle markets do not exist, disposal by landfill or an approved incinerator is acceptable. See the Magic Recycle Technical Bulletin @ www.magicinkjet.com.

USA
28 GAYLORD STREET
SOUTH HADLEY MA 01075-2894

InteliCoat Technologies

©2009 InteliCoat Technologies.®
All rights reserved.

For more information call 1-800-628-8604
or visit our web site at www.magicinkjet.com

* Most updated version of this guide can be obtained on our website.

04/07/09