

# DISPLAY FABRIC Magic® FAB-TAC-S

Polyester Woven Fabric with Low Tack PSA for Solvent

*Making all Great Images Count*



[www.magicinkjet.com](http://www.magicinkjet.com)

## MARKET APPLICATIONS

- Displays
- Window Decorations
- Window Backlits
- Wall Murals

## PRODUCT DESCRIPTION

- 6.5 mil fabric with adhesive
- Total thickness with adhesive = 12 mil
- 100% polyester woven fabric
- Low-tack, non-permanent adhesive on back side
- Removable paper liner
- Designed for use on smooth, flat, clean surfaces such as: stainless steel, aluminum, glass, styrene, polycarbonate, Plexiglas®, Sintra®, Gatorfoam®, and Fome-Core®.

## GENERAL AVAILABILITY

<u>FAB-TAC-S</u>	<u>Part #</u>
36" x 20'	70878
36" x 150'	70688
42" x 150'	70762
50" x 150'	70689
60" x 150'	70690

Core =3 inch

## FEATURES & BENEFITS

- Soft textile appearance with the added benefit of a low-tack adhesive backing for easy mounting.
- Repositionable – can be moved and reapplied
- For solvent and eco-solvent systems
- Works for backlit window displays
- Thin and lightweight

## MEDIA COMPATIBILITY

FAB-TAC-S is compatible with most solvent and eco-solvent ink jet printing systems – including Mimaki, Mutoh, Seiko, Vutek, Scitex, Nur, Roland, and Hewlett-Packard, etc.

- \* For complete Magic® product set, refer to Magic Printer Compatibility Chart under Technical Support on [www.magicinkjet.com](http://www.magicinkjet.com).
- \* For additional product details – including printer settings and lamination guidelines – see Application Guide under Tech Support of [www.magicinkjet.com](http://www.magicinkjet.com)
- \* For ICC profile availability, see [www.magicinkjet.com](http://www.magicinkjet.com)

**Phone:** 1-800-628-8604

**Fax:** 1-800-861-4128

**Disclaimer:** Information presented in this product sellsheet is intended to offer a useful reference in selecting media for your output. No media warranties are implied unless specifically mentioned. Printer and / or ink changes may affect results. The most current product information may be found at [www.magicinkjet.com](http://www.magicinkjet.com).

**Date:** March 2011

# MAGIC® PRODUCTS APPLICATIONS GUIDE

## FAB-TAC-S

InteliCoat



Digital Imaging  
Substrates

### Polyester Fabric with Low Tack Adhesive for Solvent Ink Jet Printing

MAGIC® FAB-TAC-S is an 6.5 mil, 100% polyester woven fabric for solvent ink jet printers that has a low tack pressure sensitive adhesive with a paper liner. The low tack adhesive allows FAB-TAC-S to be repositioned and reapplied countless times. This makes it ideal for displays, window decorations, window backlit and wall decal's.

#### PHYSICAL PROPERTIES

Total Caliper . . . . .	.12 mil (306 micron)
Fabric . . . . .	6.5 mil Woven 100% Polyester
Whiteness . . . . .	98
Brightness . . . . .	88
Adhesive Type . . . . .	Low Tack
Optimum Printing Environment . . . . .	70°F (30-70%RH)

#### APPLICATIONS GUIDELINES

**Printer & Ink Compatibility:** FAB-TAC-S may be printed in most solvent and eco-solvent printing systems such as: Mimaki JV3, Mutoh Toucan, DGI, Vutek, Nur, Roland Versa Camm, Roland XC, etc. For specific printer compatibility, refer to the Magic Printer Compatibility Chart under Technical Support on [www.magicinkjet.com](http://www.magicinkjet.com).

**Printer Settings:** Optimized print settings will vary from printer manufacturers. Recommended ink saturation level is 350%. Recommended heater setting of 45° C for the pre heater and 40° C for the post heater. These settings have been found to be a good starting point. Use maximum dryer heat on exit.

**Color Calibration:** ICC color profiles can be obtained for selected RIP, ink and printer combinations on the [magicinkjet.com](http://magicinkjet.com) web site. If the proper solutions are not available, periodically check the web page for current availability, as new profiles are being developed on an on-going basis.

**Water Resistance & Surface Protection:** Let image dry 24 hours before exposing to moisture. Dirt and stains can not be cleaned from the image surface. Surface protection is recommended to protect the surface from dirt and abrasion. Excessive folding or creasing can damage the imaged surface.

**Material Handling & Storage:** Once print is completed, roll imaged media (with the graphics facing inward) onto a core until ready for use. Folding of the material is not recommended. Unimaged material should be stored at 72° F (+/-5°) for no longer than 1 year, to obtain maximum adhesion values. After use, the product should be stored in its original packaging in the poly bag.

#### FINISHING RECOMMENDATIONS

**Surface Preparation:** Always ensure that the receiving surface is thoroughly cleaned, free of dust, dirt or cleaner residues. Painted metal, glass and standard graphic art mounting boards surfaces should be cleaned with standard glass cleaner or isopropyl alcohol (IPA). Most surfaces may be cleaned with a damp warm cloth. Painted surfaces should be painted with a latex paint containing no wax's or silicone. Always pretest you application surface prior to installation.

**Recommended Application Surfaces:**

Painted metal	Plexi Glass	Gatorlite® Black	Gatorplast® Black	Sintra® board
plastic	textured walls	non-painted metal	glass	acrylic
polycarbonate	flat or slightly curved surfaces	stainless steel	Painted dry wall	

\*\*not recommended for highly porous, fibrous surfaces. Textured wall paper, cardboard, and wood would be examples.

**Installation Techniques:** Proper contact of the adhesive to the mounting substrate is critical. For installations by hand, use application tape and a squeegee with sufficient pressure. It is not recommended to use water during installation.

**Removal:** When removing FAB-TAC-S from any surface, remove slowly and lift at a 90° angle. Different surfaces have different adhesive characteristics. If removal leaves a residue, use soapy water and a cloth to remove any adhesive, Isopropyl alcohol (IPA) or rubbing alcohol may be used. Always pretest first.

USA  
28 GAYLORD STREET  
SOUTH HADLEY MA 01075-2894  
©2010 InteliCoat Technologies.  
All rights reserved.

*InteliCoat Technologies*

For more information, call 1-800-628-8604  
or visit our website: [www.magicinkjet.com](http://www.magicinkjet.com)

\*Most updated version of this guide can be obtained on our website.