



# MAGIC POSPRO+400

16.5 mil anti curl blackout film (*matte*)

**PRINTER COMPATIBILITY**



**DESCRIPTION**

Magic POSPRO+400 blackout film with a bright white matte surface producing vibrant, high quality images and unmatched durability. Ideal for the production of panels for portable trade show booths and durable semi rigid POP displays.

**PHYSICAL CHARACTERISTICS**

Thickness of Film	16.5 mil
Basic Weight	420 g/m <sup>2</sup>
Opacity	100%
Whiteness	112
Finish	Matte

*\*All values are targets*

**FEATURES AND BENEFITS**

- Proprietary base film
- Award winning Magic® “UNIVERSAL” coating
- Excellent color gamut and black density
- Low glare matte finish
- Tear resistant
- Water resistant
- Scratch resistant
- Fade resistant
- Bright white
- Lay flat
- Compatible with most PSA and thermal overlaminates

**COMMON APPLICATIONS**

- Rollup banners
- Hanging banners
- General posters
- General signage
- Retail advertising
- Tradeshow and installation graphics

**PROCESSING TIPS**

- Preferred side out

**FINISHING & PRINTING**

- Suggested heater settings for solvent / eco solvent:
- pre-heat 25°C
- print/post heat 35°C
- Visit [www.magicinkjet.com](http://www.magicinkjet.com) for media profiles

**SHELF LIFE**

2 years from ship date

**STORAGE CONDITIONS**

Temperature	50-85° F (10-30° C)
Relative Humidity	30-65%

**OPTIMAL PRINTING ENVIRONMENT**

Temperature	50-85° F (10-30° C)
Relative Humidity	30-65%

